

Comment: samples from ACME July 22, 2018

| Spring # | Rank | Seated Force | Open Force | Clearance | Bind Ht | Spring Rate | Errors       |
|----------|------|--------------|------------|-----------|---------|-------------|--------------|
| 1        | 1    | 90.2         | 150.0      | .604"     | .856"   | 110.8 lb/in | Errors: None |
| 2        | 13   | 90.0         | 149.9      | .604"     | .856"   | 110.9 lb/in | Errors: None |
| 3        | 5    | 90.1         | 150.1      | .603"     | .857"   | 111.0 lb/in | Errors: None |
| 4        | 12   | 90.0         | 149.9      | .605"     | .855"   | 111.0 lb/in | Errors: None |
| 5        | 4    | 90.1         | 150.1      | .604"     | .856"   | 111.0 lb/in | Errors: None |
| 6        | 11   | 90.0         | 150.0      | .605"     | .855"   | 111.1 lb/in | Errors: None |
| 7        | 3    | 90.1         | 150.0      | .605"     | .855"   | 111.0 lb/in | Errors: None |
| 8        | 10   | 90.0         | 150.0      | .605"     | .855"   | 111.1 lb/in | Errors: None |
| 9        | 2    | 90.1         | 150.0      | .605"     | .855"   | 110.9 lb/in | Errors: None |
| 10       | 9    | 90.1         | 150.0      | .605"     | .855"   | 110.8 lb/in | Errors: None |
| 11       | 8    | 90.1         | 149.9      | .605"     | .855"   | 110.7 lb/in | Errors: None |
| 12       | 15   | 90.0         | 149.8      | .605"     | .855"   | 110.7 lb/in | Errors: None |
| 13       | 7    | 90.1         | 149.9      | .604"     | .856"   | 110.7 lb/in | Errors: None |
| 14       | 14   | 90.0         | 149.8      | .605"     | .855"   | 110.8 lb/in | Errors: None |
| 15       | 6    | 90.1         | 149.7      | .604"     | .856"   | 110.5 lb/in | Errors: None |
| 16       | 16   | 89.9         | 149.7      | .604"     | .856"   | 110.6 lb/in | Errors: None |